

H2M0040120D

Silicon Carbide Power MOSFET

N-Channel Enhancement Mode

Features

- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Easy to Parallel and Simple to Drive
- Avalanche Ruggedness
- Halogen Free, RoHS Compliant

Benefits



- Higher System Efficiency
- Reduced Cooling Requirements
- Increased Power Density
- Increased System Switching Frequency

Applications

- Solar Inverters
- Switch Mode Power Supplies
- High Voltage DC/DC Converters
- Battery Chargers
- Motor Drives

- Pulsed Power applications

Package



Part Number	Package
H2M0040120D	TO-247-3

Maximum Ratings ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note
V_{DSmax}	Drain - Source Voltage	1200	V	$V_{GS}=0V, I_D=100\mu A$	
V_{GSmax}	Gate - Source Voltage	-10/+25	V	Absolute maximum values	
V_{GSop}	Gate - Source Voltage	-5/+20	V	Recommended operational values	
I_D	Continuous Drain Current	60 40	A	$V_{GS}=20V, T_c=25^\circ\text{C}$ $V_{GS}=20V, T_c=100^\circ\text{C}$	
I_{DM}	Pulse Drain Current	140	A	Pulse width limited by T_{jmax}	
P_D	Power Dissipation	310	W	$T_c=25^\circ\text{C}, T_j=150^\circ\text{C}$	Fig. 11
T_j, T_{stg}	Operating Junction and Storage Temperature	-55 to +150	$^\circ\text{C}$		

Package Dimensions: TO-247-3L

